

# CableMaster 500

optimize!  
**softing**



## CABLE TESTER

IT Networks



[itnetworks.softing.com](http://itnetworks.softing.com)

# CableMaster 500

The **CableMaster500** combines continuity testing, mapping, generating tones and length measurement functions into a single easy-to-use unit for installation, troubleshooting, and maintenance for telco, network, or coax cable. The backlit display, glow-in-the-dark keypad and a built-in flashlight helps you to work in the dark.

Whether your jobs are commercial or residential, the versatility and added features of the CableMaster500 makes it a best value cable verifier for the professional installer!

## Key Features


- Detects Open, Shorts, Miswires, Reverses & Split Pairs
- Tests to T568A/B wiremap configuration: shorts, opens, miswires, reverses and split pairs
- Single-ended Testing for Shorts & Split Pairs
- Measures Length in Feet/Meters
- Identifies cable location on active ports using flashing Port Link Light
- Easy to read, backlit LCD screen with large icons, glow-in-the-dark keypad and built-in LED flashlight for use in dark areas
- Verifies continuity for multiple cable types (LAN, Phone and Video)
- Audible beep for additional feedback
- Identify up to 20 network or coax cable runs at a time
- Measures cable length, distance to opens and breaks specific wires, pairs or all wires simultaneously
- Master remote stored in main unit
- Voltage detection warning icon
- Continuous loop test mode for trouble shooting
- Auto-off and timed backlight in any mode for low power consumption and long battery life
- Audible Tone Generator, 4 selectable cadences




Easy to read, backlit LCD screen with large icons, glow-in-the-dark keypad and built-in LED flashlight for use in dark areas




# Sample Screen Shots



Pass



Open and Short



Port Link Light

# Cable Tester Specifications

<b>Display</b>	Large 2.75" Backlit Monochrome LCD
<b>Dimensions</b>	6.8" x 3.2" x 1.4" (17.3 x 8.1 x 3.5 cm)
<b>Weight</b>	10.8 oz. (305 grams) with battery and remote
<b>Operating Temperature</b>	0°C/32°F to 50°C/122°F
<b>Storage Temperature</b>	-20°/-4°F to 60°C/140°F
<b>Humidity</b>	10% to 90%, non-condensing
<b>Maximum Voltage between any two connector pins without damage</b>	RJ12/RJ45/F: 50V DC or AC
<b>Battery Life</b>	9V alkaline battery typical Standby: 4 years Active: 425 hours
<b>Cable Types:</b>	Shielded or Unshielded; CAT7, CAT6A, CAT5e, CAT5, CAT4, CAT3, Coax
<b>Maximum RJ Cable Length Testing</b>	0 to 1,000 feet (305 meters)
<b>Minimum Cable Length for Split Pair Detection</b>	1.5 feet (0.5 meters)
<b>Maximum Coax Cable Length</b>	Varies depending on cable resistance varies
<b>Low Battery</b>	Icon flashes when battery voltage falls below 6V
<b>Measurement Technology</b>	Capacitance testing
<b>Length Accuracy Without Length Constant</b>	± 3% plus + 1 foot
<b>Default Length Constant (Restored with power on reset)</b>	Voice (Twisted pair): 17.4 pF/ft Video (Coax): 16.5 pF/ft Data (Twisted pair): 15 pF/ft
<b>Warranty</b>	Limited 1 yr

**NORTH AMERICA & CANADA**

Softing Inc.  
Knoxville, Tennessee  
Phone: +1.865.251.5252  
E-mail: sales@softing.us

**ASIA/PACIFIC**

Singapore  
Softing Singapore Pte. Ltd.  
Singapore  
Phone: +65-6569-6019  
E-mail: asia-sales.itnetworks@softing.com

**China**

Softing Shanghai  
Shanghai  
Phone: +86-21-54133123  
E-mail: china-sales.itnetworks@softing.com

**EUROPE/MIDDLE EAST/AFRICA**

Germany  
Softing IT Networks GmbH  
Haar, Munich  
Phone: +49 89 45 656 660  
E-mail: info.itnetworks@softing.com

**France**

Softing SARL  
Créteil, Île-de-France  
Phone: +33 1 45 17 28 05  
E-mail: info.france@softing.com

**Italy**

Softing Italia Srl.  
Cesano Boscone, Milano  
Phone: +39 02 4505171  
E-mail: info@softingitalia.it


**Austria**

Buxbaum Automation GmbH  
Eisenstadt  
Phone: +43 2682 7045 60  
E-mail: office@myautomation.at

For technical information and support please  
contact the Softing office in your country.

<http://itnetworks.softing.com>

For more information please contact:



©2017 Softing IT Networks GmbH. In line with our policy of continuous improvement and feature enhancement, product specifications are subject to change without notice. All rights reserved. Softing and the Softing Logo are trademarks or registered trademarks of Softing AG. All other trademarks, registered or unregistered, are sole property of their respective owners.

