

Professional Office/Contact Centre Headsets



Order Code
JPL-611-PM

Order Code
JPL-611-PB



TECHNICAL DATA

Microphone:	
Impedance:	2.2kΩ
Sensitivity:	-32dB ± 3dB at 1kHz
Directivity:	Bi-directional
Frequency Range:	50Hz~20kHz ± 6dB
Distortion:	Less than 3%
Power Supply:	3V DC
S/N Ratio:	More than 58dB
Speaker:	
Impedance:	150Ω ± 15% at 1kHz
Sensitivity:	93 ± 3dB at 1kHz 60mV Input
Max Input Power:	100mV
Frequency Range:	100Hz~6,800Hz
Distortion:	Less 3% at 1kHz 60mV



PLX COMPATIBLE QD



CLOTHING CLIP & HANGING HOOK



HEADSET CASE



JPL-611

Featuring a contact centre designed microphone boom arm with improved clarity and noise cancelling.

Overview

Features	Single or dual ear Left / right ear side compatible Surround Shield™ noise cancelling microphone with static shock protection Wideband enabled speakers with Sound Shield™ acoustic shock protection 'Put and stay' ratchet microphone boom arm Overhead, sure-fit fully adjustable headband with optional padded headband for additional comfort Fitted with large 50mm leatherette ear cushions for maximum all day comfort
What's included	Headset Tough Case, headset hanging hook, Clothing clip and Quick Start Guide
Headset Weight	~ 62g / ~94g
Connection	PLX fitted as standard or GN** compatible QD options
Compatibility	For full range of bottom leads* and compatibility information - Go to Jpltele.com
Certifications	UKCA, CE, FCC, EAN, RoHS, REACH
Warranty	3 Years Warranty - includes 2 years standard no quibble repair or replace warranty PLUS a 3rd year cover on all non-moving parts
MOQ	Master Shipping Carton: 32
EAN:	JPL-611-PM: 5060126956822, JPL-611-PB: 5060126956839
SKU:	JPL-611-PM: 575-121-001, JPL-611-PB: 575-121-002

PLX = Plantronics compatible QD
E&OE

* optional to purchase separately.
** GN QD available on special request

