



ULiQ for Surge Protective Devices



Surge Protective Devices

E326289

Guide Information

Citel America Inc

10108 USA Today Way, Miramar FL 33025

Cat No(s): DS41-230%

| <u>SPD</u> <u>Type</u> | <u>Volts</u> <u>(V)</u> | <u>AC/DC</u> <u>DC PV</u> | <u>Phase</u> | <u>Amps</u> <u>(A)</u> | <u>Ambient</u> <u>Min(°C)</u> | <u>Ambient</u> <u>Max(°C)</u> | <u>Mode</u> | <u>VPR</u> <u>(Vpk)</u> | <u>MLV</u> <u>(Vpk)</u> | <u>MCOV</u> <u>(V)</u> | <u>Vn</u> <u>(Vdc)</u> | <u>In</u> <u>(kA)</u> | <u>SCCR</u> <u>(kA)</u> | <u>Notes</u> |
|---------------------------|----------------------------|------------------------------|--------------|---------------------------|----------------------------------|----------------------------------|-------------|----------------------------|----------------------------|---------------------------|---------------------------|--------------------------|----------------------------|--------------|
| 4CA (5) | 230 | AC | 3Y | N/A | -35 | 60 | L-G | - | 1600 | 275 | N/A | 20 | N/A | 2 |
| 4CA (5) | 230 | AC | 3Y | N/A | -35 | 60 | L-G | - | 1600 | 275 | N/A | 10 | N/A | 2 |

Evaluated to: UL 1449 4th Ed. Rev: 2016-03-17 and CSA Electrical Certification Notice 516/CSA C22.2 No. 8 13

% - May be followed by S

- - L-L modes may also be labeled as L-N modes

Note 2 - Suitable for Field and Factory wiring.

Where a minimum ambient temperature is not specified, assume 0°C unless the product is marked otherwise or with an Outdoor use Environmental Rating. See Electrical Equipment for Use in Ordinary Locations (AALZ) for details regarding Environmental Ratings.

Report

Date: 2010-02-25

Last 2016-04-18

Revised:

© 2018 UL LLC

