

## LS60L

### Battery-Powered Knockout Punch Driver

Lithium-Ion Power



## ***The Easy Way to Drive Knockout Punches***

The Greenlee LS60L Battery-Powered Knockout Punch Driver is now part of the new line of Greenlee “L” Series Gator tools with Lithium-Ion power. It makes the holemaking process even easier than before.

### ***More Power***

- State of the art 18V lithium-ion (Li-ion) battery provides 70% more cycles per charge and faster cycle times—punch a hole for 2” conduit in about 10 seconds.
- Available with 120V, 12V, or 230V battery charger or with 120V or 230V corded adapter in place of batteries and charger.

### ***More Intelligent***

- LED light provides the operator with the battery charge and tool maintenance status.

- Smart battery chargers control the charging current, charging voltage and battery temperature to maximize battery life.

### ***More Ergonomic***

- Forward handle position improves tool balance.
- One trigger controls all tool functions.
- Overmolded tacky grip areas make gripping the tool easier and more comfortable.
- LED work light illuminates dark work areas.

### ***More Green***

- LS60L tools use biodegradable oil.

## Features

- Capable of punching up to 2" conduit (61.5 mm) size holes in 10-gauge (3.5 mm) mild steel and 12-gauge (2.5 mm) stainless steel.
- Punches a hole for 2" conduit (61.5 mm) in only 10 seconds.
- Tool senses when the hole is completely punched and automatically shuts off to prevent damage to the punch and die.
- 18V 3.0 Ah lithium-ion battery.
- Ergonomic forward position handle with overmolded tacky grip area.
- LED battery condition monitor to improve jobsite productivity.
- LED work light to help you see in poorly lit or tight spaces.
- All battery-powered tools include a molded carrying case, 2 batteries, and either a 120V, 12V, or 230V battery charger. All tools with corded adapters include a molded carrying case and either a 120V or 230V corded adapter.

## Specifications

LS60L Specifications	
Length:	11-1/2" (292 mm)
Width:	2-7/8" (73 mm)
Height:	12-1/2" (318 mm)
Weight:	8.8 lbs. (4.0 kg)
Estimated Cycles Per Charge:	300
Capacity:	10 gauge mild steel: 2" conduit (61.5 mm) 12 gauge stainless steel: 2" conduit (61.5 mm)

## Ordering Information

CAT #	UPC #	DESCRIPTION	QTY
LS60LA11	52155	Battery Punch Driver-120 Volt Charger with 2 draw studs, 1 adapter and 1 spacer	1
LS60LA12	52156	Battery Punch Driver-12 Volt Charger with 2 draw studs, 1 adapter and 1 spacer	1
LS60LA22	52157	Battery Punch Driver-230 Volt Charger with 2 draw studs, 1 adapter and 1 spacer	1
LS60LB11	52158	Battery Punch Driver-120 Volt Charger with 1/2" through 2" Slug-Buster® conduit size punches, 2 draw studs, 1 adapter and 1 spacer	1
LS60LB12	52159	Battery Punch Driver-12 Volt Charger with 1/2" through 2" Slug-Buster® conduit size punches, 2 draw studs, 1 adapter and 1 spacer	1
LS60LB22	52160	Battery Punch Driver-230 Volt Charger with 1/2" through 2" Slug-Buster® conduit size punches, 2 draw studs, 1 adapter and 1 spacer	1
LS60LA120	52161	Punch Driver-120 Volt AC Adapter with 2 draw studs, 1 adapter and 1 spacer	1
LS60LA230	52162	Punch Driver-230 Volt AC Adapter with 2 draw studs, 1 adapter and 1 spacer	1
LS60LB120	52163	Punch Driver-120 Volt AC Adapter with 1/2" through 2" Slug-Buster® conduit size punches, 2 draw studs, 1 adapter and 1 spacer	1
LS60LB230	52164	Punch Driver-230 Volt AC Adapter with 1/2" through 2" Slug-Buster® conduit size punches, 2 draw studs, 1 adapter and 1 spacer	1

### DISTRIBUTOR INFORMATION:

USA  
Tel: 800.435.0786  
Fax: 800.451.2632

Canada  
Tel: 800.435.0786  
Fax: 800.524.2853

International  
Tel: +1.815.397.7070  
Fax: +1.815.397.9247

