

Paladin[®] Tools

1600 Series Crimper- *Professional*

- Low hand force & superior crimp force
- True ergonomic soft, rubber handles
- Precision calibrated crimp profiles
- Powerful & precise - the tool does the work, not your hand
- Lifetime warranty

1645

30-18 AWG

- Frame Only
- HDTV
- 50/75 ohm Coax
- Fiber Optic
- Insulated Terminals
- Non-Insulated Terminals
- Open Barrel Contacts
- D-Sub Contacts
- Wire Ferrules


Paladin Tools®

LIMITED
LifeTime
WARRANTY

1600 Series Crimper- Professional

Item #	Dies	Cable Type	Connector Type	Crimp Sizes (inches)
PA1600	N/A	-	Crimp tool frame only	N/A
PA1609	PA2660	Belden 8281 & 7505	BNC/TNC, HDTV	.324/.068 HEX, .042 SQ
PA1611	PA2661	RG59, Belden 1505A & 8241	BNC/TNC, HDTV	.255/.068 HEX, .042 SQ
PA1612	PA2662	RG6, Belden 1694A & 1855A	BNC/TNC, HDTV	.275/.178 HEX, .042 SQ
PA1613	PA2663	Belden 1694A, (8218) & NT735	BNC/TNC, HDTV	.278/.197 HEX, .042 SQ
PA1616	PA2003	RG174/(RG179/188), & other small	BNC/TNC	.178/.068 HEX, .042 SQ
PA1617	PA2005	RG58/59/62AU	BNC/TNC	.255/.213/.068 HEX
PA1619	PA2019	RG59, RG62AU & (Belden 8281/8241)	BNC/TNC	.324/.255/.068 HEX
PA1669	PA2683	Belden 1855A, 1865A, 1505A, 1505F, 1694A, 1694F, 179DT	BNC/TNC, HDTV	.278/.255/.178/.041 HEX
PA1606	PA2044	Fiber Optic	Lucent SC-Type	.190 HEX, .105/.09 RND
PA1614	PA2664	Fiber Optic	SMA/SMB/FC/Biconic Fiber	.213/.178/.151 HEX
PA1668	PA2668	Fiber Optic	3M, Fiber Source Suncall SC & ST	.120/.137/.190 RND
PA1605	Fixed	22-14 AWG	Insulated Terminals & Lugs	Standard commercial
PA1618	Fixed	20-10 AWG	Non-Insulated Terminals & Lugs	Standard commercial
PA1631	Fixed	24-14 AWG	Open Barrel Contacts, F-type	Molex, Waldom, Leoco, etc. type
PA1645	Fixed	30-18 AWG	Open Barrel Contacts, F-type	Molex, Waldom, Leoco AMP (Tyco) type
PA1646	Fixed	28-20 AWG	Open Barrel D-sub Contacts	Standard pins
PA1647	PA2681	20-10 AWG	Insulated & Non-Insulated Wire Ferrules	DIN or US-type
PA1648	Fixed	20-12 AWG	Insulated & Non-Insulated Wire Ferrules	DIN or US-type
PA1649	Fixed	10-6 AWG	Insulated & Non-Insulated Wire Ferrules	DIN or US-type

Crimp tool shown for example purposes only.



Operating Instructions:

1. Adjust desired ratchet force by removing screw from the gear. Rotate the gear toward "-" to decrease force, and towards "+" to increase force. Replace the screw when desired setting is found.
2. Assemble cable with connector attached to it. Install assembly into the appropriate crimp die section. Squeeze handles closed through full ratchet cycle until they automatically open.
3. In case of error when initiating a crimp cycle, push the ratchet safety release trigger forward toward the jaws to release the crimp.

Notes:

1. Fixed dies are permanently installed and calibrated by the factory. Do not remove.
2. Removal of fixed 1600 dies will void warranty.
3. Return to factory for all maintenance requirements. Taking tool apart or servicing by unauthorized dealer will avoid warranty

1645

HTF 36:30-18awg, Open Barrel



Made in Taiwan WO#98783

Paladin Tools®

Phone: 800.272.8665
Int'l Phone: 001.804.550.1121
Website: www.paladin-tools.com