



Intuitive control of meeting and video conference rooms



Simple control

Control all room functions through iOS or Android touch devices, or via Safari and Chrome browsers

Integrating video conference

The AIFa II is a perfect choice for video conference and with a few clicks your meeting is on.

NEB - Neets Expansion Bus

NEB bus added for expansion with for example NEB Keyboard to increase ease of use (Optional feature)

Control the room

Control additional equipment such as lighting, HVAC, audio volume, and other room functions

Neets Control – AIFa II provides comprehensive yet intuitive control of AV equipment in meeting- and conference rooms. AIFa II is easily configured and installed, and provides end users with one-touch control of a multitude of AV and additional device functions. All functions controllable by AIFa II are available via a touch-screen panel on an Apple iOS or Android mobile device, or by a PC running Safari or Chrome.

By adding NEB keyboard, level control and NEB Expansion to the AIFa II gives you the opportunity to control your AV-equipment and makes it easy to use through the same interface and recognizable custom graphical user interface.

The compact 1U rack mount frame provides status monitoring with front panel LED indicators, and the rear panel allows easy access for connecting all necessary cables for control and configuration, ensuring that installation and servicing of AIFa II will be straightforward, fast and efficient.

The AIFa II is well suited for integrating video conference into your meeting rooms and makes it very easy to control both your AV-equipment and video conference with a tablet. Neets Control - AIFa II makes video conferencing easy to use and help you increase your productivity.

Features:

Easy configuration through drag 'n drop with Neets Project Designer software


Custom graphical user interface design (GUI)

Front panel with LED indication

Built in potential free relays with IEC Mains Adaptor option

NEB - Neets Expansion Bus gives you extra panels in the room to control your AV-equipment. (Optional feature)

Control devices through LAN



Technical specifications:

Communication Ports:

3 X RS-232 (tx/rx) / IR (x2)
2 X RS-232 (tx) / IR (x2)

RS-232:

Baud: 1200 – 115200
Data bit: 7/8
Parity: none, even, odd
Stop bit: 1, 2

IR:

Transmit
400 Hz – 500 khz
Devices: 10

Input/ output ports:

24 x input/output ports

Input:

Sense low: <1 VDC
Sense high: >4 VDC

Output:

Type: open drain
Max voltage: 24 VDC
Max current: 0.5A

LAN:

Devices: 10

NEB:

1 X NEB (5 units)
(NEB Keyboard, Level Control, Port Expansion)

Built-in relays:

4 X potential free (assignable)
Power capacity: 240 VAC/ 8A
Note: contact neets for screen sizes above 3 m

Included in box:

1 X 240V IEC cable

Dimensions:

Width: 437 mm/ 483 mm
Height: 44 mm (1U)
Depth: 141 mm

Weight:

1.9 Kg

Ac line input:

100 – 240 V

Conformity:

CE
Approval:
EN 61000-6-1
EN 61000-6-2

Item number:

310-0301:
Neets Control - AIFa II, black