Professional Office/Contact Centre Headsets





TECHNICAL DATA

Microphone:

Impedance: $2.2k\Omega$

Sensitivity: $-32dB \pm 3dB$ at 1kHz Directivity: Bi-directional Frequency Range: $50Hz\sim20kHz\pm6dB$ Distortion: Less than 3% Power Supply: 3V DC More than 58dB S/N Ratio:

Speaker:

 $150\Omega \pm 15\%$ at 1kHz Impedance: Sensitivity: 93 ± 3dB at 1kHz 60mV Input

Max Input Power: Frequency Range: 100Hz~6,800Hz Distortion: Less 3% at 1kHz 60mV







PLX OR GN COMPATIBLE QD

50mm CUSHION & CLOTHING CLIP

HEADSET CASE & HANGING HOOK









JPL-612

Featuring an aluminium bracket housing and large 70mm leatherette ear cushions.

Overview

| Features | Single or dual ear |
|-----------------|--|
| | Left / right ear side compatible |
| | Alumimium bracket casing the speaker housing for additional strength |
| | Surround Shield™ noise cancelling microphone with static shock protection |
| | Wideband enabled speakers with Sound Shield™ acoustic shock protection |
| | 'Put and stay' ratchet microphone boom arm |
| | Overhead, sure-fit fully adjustable headband |
| | Fitted with large 70mm leatherette ear cushions for maximum all day comfort, 50mm leatherette ear cushion supplied as spare |
| What's included | Headset Tough Case, spare 50mm leatherette ear cushions, headset hanging hook, Clothing clip and Quick Start Guide |
| Headset Weight | ~74g/~108g |
| Connection | PLX fitted as standard or GN** compatible QD options |
| Compatibility | For full range of bottom leads* and compatibility information - Go to Jpltele.com |
| Certifications | CE, RoHS, REACH |
| Warranty | 3 Years Warranty - includes 2 years standard no quibble repair or replace warranty PLUS a 3rd year cover on all non-moving parts |
| MOQ | Master Shipping Carton: 32 |
| EAN: | JPL-612-PM: 5060126956426, JPL-612-PB: 5060126956433 |
| SKU: | JPL-612-PM: 575-281-001, JPL-612-PB: 575-281-002 |

PLX = Plantronics compatible QD

* optional to purchase seperately. ** GN QD available on special request





















